


Round Tapered Aluminum Poles



Catalog Number	Description				Maximum EPA		
	Height	Diameter	Bolt Circle	Anchor Bolts	80 MPH	90 MPH	100 MPH
RTA-20-5.0-156-**-**	20	5.0 X 3.0	Consult Factory 5.6		6.6	4.6	3.2
RTA-20-6.0-188-**-**	20	6.0 X 4.0			14.4	10.8	8.5
RTA-25-6.0-188-**-**	25	6.0 X 4.0			8.6	6.1	4.6
RTA-25-8.0-156-**-**	25	8.0 X 4.5			16.7	12.8	10
RTA-30-8.0-188-**-**	30	8.0 X 4.5			14.6	11.1	8.6
RTA-30-10.0-188-**-**	30	10.0 X 6.0			28	21.5	16.8
RTA-35-8.0-188-**-**	35	8.0 X 4.5			9.8	7.1	5.3
RTA-35-10.0-188-**-**	35	10.0 X 6.0			21.1	16	12.2
RTA-40-8.0-250-**-**	40	8.0 X 4.5			11.4	8.4	6.4
RTA-40-10.0-250-**-**	40	10.0 X 6.0			---	consult factory	---

Nut covers standard.

3" x 5" hand hole on 5" and 6" diameter poles - all others 4" x 6".

Vibration dampener standard on poles 25' and greater.

When mounting 3 or more fixtures, pole top must be 3" or greater.

Round Straight Aluminum Poles



Catalog Number	Description					Maximum EPA		
	Height	Diameter	Bolt Circle	Anchor Bolts	Pole Weight	80 MPH	90 MPH	100 MPH
RSA-8-4.0-125-**-**	8	4.0	Consult Factory 25		11.2	8.6	6.8	
RSA-10-4.0-125-**-**	10	4.0			29	8.2	6.1	4.7
RSA-12-4.0-125-**-**	12	4.0			33	6.0	4.3	3.2
RSA-14-4.0-125-**-**	14	4.0			37	4.1	2.8	1.9
RSA-16-4.0-125-**-**	16	4.0			43	2.8	1.6	1.0
RSA-18-5.0-125-**-**	18	5.0			48	4.3	3.1	2.4
RSA-18-5.0-188-**-**	18	5.0			58	8.0	6.8	4.7
RSA-20-5.0-125-**-**	20	5.0			54	3.0	2.1	1.5
RSA-20-5.0-188-**-**	20	5.0			82	6.4	4.8	3.6

2-3/8" x 4-1/2" hand hole opening in 4" dia., 3" x 5" hand hole for all others.

Nut covers standard.